

# TRIPODS

## LIGHTWEIGHT TRIPOD



The Didsbury Lightweight Tripod provides an easy to handle hoist mounting for vertical lifts in restricted access situations. Easy to erect and adjustable for height and level, it can be deployed quickly for man-riding, general lifting and rescue operations. When not in use the tripod packs away neatly in its own compact carrying bag.

**PART NOS. L/W TRIPOD 61/960  
CARRY BAG 61/927**

### FEATURES

- Manufactured in corrosion-resistant aluminium it offers excellent strength-to-weight characteristics and exceptional durability
- Quick release leg splay latch incorporated into head mountings - simply pull on the legs to release
- Self limiting leg position improves safety and access by eliminating the need for potentially dangerous restraining chains or obstructive tie bars
- Each leg is telescopically adjustable for height and level
- Quick release spring clip pins are easy to operate and secure
- Swivelling feet with rubber slip-resistant tread for use on smooth surfaces and spike profile to locate securely in soft ground
- Two universal eyebolts suit most hoists and fall arrester mountings
- Packs into its own carrying bag for safe and convenient transportation
- Proof loaded, tested and certified for man-riding and materials handling roles
- Provides exceptionally lightweight, free-standing lifting system when used with the Didsbury Deco 2000 compact hoist
- Tested to BS EN 795 for protection against falls from height

### WORKING LOAD LIMITS WWL:

Materials handling: 508kgs at 5:1 safety factor

Man-riding: 254kgs at 10:1 safety factor

### DIMENSIONS:

Overall height

Max extended: 2.4m. Will service a manhole diameter of 2.2m or a trench width of 1.6m

Min extended: 1.37m. Will service a manhole diameter of 1.15m or a trench width of 0.85m

Min folded: 1.49m

### ADJUSTMENTS:

5 positions at maximum and minimum extended in 50mm increments

### WEIGHT:

18kgs

### DIDSBURY ENGINEERING CO. LTD.

LOWER MEADOW ROAD, BROOKE PARK, HANDFORTH, WILMSLOW, CHESHIRE, SK9 3LP

TEL: +44(0)161 486 2200 FAX: +44(0)161 486 2211 EMAIL: ca@didsbury.com WEB: www.didsbury.com

